

LOW-LIGHT

HI-SPEED

SMART

RELIABLE

IQeye700/750 series

MEGAPIXEL NETWORK CAMERAS



IQeye700 and IQeye750 Day/Night

Choose the IQeye700 for normal indoor/outdoor scenes and the IR Sensitive IQeye750 Day/Night for very low-light applications.

IQeye700/750 Series megapixel network cameras deliver best-in-class image quality, dynamic range and network stability you can rely on in the most challenging environments. These full featured cameras provide incredible hi-speed IQeye Resolution™ with exceptional low-light performance in a rugged, industrial compact package.

The IQeye700/750 delivers low-bandwidth video for remote viewing while simultaneously recording crisp, clear megapixel images. IQinVision continues to lead the industry in image quality, reliability and advanced camera features like PoE, on-camera storage and the Public View Port™ which makes focusing simple and integrates easily with legacy CCTV systems.


IQeye cameras are the smart solution ...
so you never miss a thing.

www.iqeye.com

IQinvision 

When you can't afford to miss a thing.

IQeye700 and IQeye750 Day/Night Cameras



High Resolution



IQeye Resolution

IQrecorder™

Available with every IQeye, IQrecorder enables you to record and playback crisp, clear IQeye Resolution™ images using affordable network storage *with no client software.*



IQauthenticate™

Every IQeye is also available with on-camera, digital authentication that protects images right in the camera. IQauthenticate addresses the image manipulation problem, *at the source*, ensuring your evidence has not been compromised.



IQeye 700/750 back panel

- 1.3 Mpix resolution @ up to 30 ips
- 2.0 Mpix resolution @ up to 20 ips
- 3.1 Mpix resolution @ up to 12 ips
- 5.0 Mpix resolution @ up to 10 ips
- < 0.05 lux IR Sensitive (750 Series)
- MultiStream low BW + hi resolution
- IEEE 802.3af - Power-Over-Ethernet
- Public View Port™ analog output
- CF slot for on-camera recording
- LIGHTGRABBER II™ low-light feature
- Digital image cropping
- Include/Exclude exposure window
- Alarm IO
- Wide operating temperature range
- < 2.5 watts power AC/DC
- Privacy zones
- Auto, manual and scheduled day/night settings

CAMERA MODEL	LENS OPTIONS	POWER SUPPLY	ENCLOSURE
IQ70x Series  IQ711 - 1.3 MP Camera, 30ips, 0.1 lux IQ702 - 2.0 MP Camera, 20ips, 0.2 lux IQ703 - 3.1 MP Camera, 12ips, 0.3 lux IQ705 - 5.0 MP Camera, 10ips, 0.3 lux	NL - No Lens V1 - Wide Varifocal Lens V2 - Telephoto Varifocal Lens V3* - Wide Varifocal Lens <i>(Only compatible with IQ711)</i> V4* - Telephoto Varifocal Lens <i>(Only compatible with IQ711)</i> V7 - Wide Varifocal 3MP IR Corrected Lens	NP - No Power Supply PE - IEEE 802.3af PoE Module	NE - No Enclosure
IQ75x Day/Night Series  IQ752 - 2.0 MP Day/Night Camera, 20ips IQ753 - 3.1 MP Day/Night Camera, 12ips IQ755 - 5.0 MP Day/Night Camera, 10ips	NL - No Lens V5 - Wide Varifocal Lens V6 - Telephoto Varifocal Lens V7 - Wide Varifocal 3MP IR Corrected Lens	NP - No Power Supply PE - IEEE 802.3af PoE Module	NE - No Enclosure
Example - IQ753NLNPNE - 3.1 MP Day/Night Camera, 12ips, No Lens, No Power Supply, No Enclosure Part Number - IQ753 ⇒ NL ⇒ NP ⇒ NE			

CONTACT IQINVISION FOR A COMPLETE LIST OF KITS AND ACCESSORIES.
 Camera dimensions (without lens) approx. 2.52"(6.4cm)H x 2.52"(6.4cm)W x 3.94"(10.0cm)D
 Camera weight (without lens) 13oz (368.5g)
 For shipping weight information, please contact IQinVision.

©2008 IQinVision, Inc., IQinVision, IQeye logo are registered trademarks, and IQeye, Public View Port, IQauthenticate, IQrecorder, Resolution-On-Demand, IQeye Resolution and LIGHTGRABBER are trademarks of IQinVision. All other brands, trademarks and/or registered trademarks are property of their respective holders. 0408

When you can't afford to miss a thing.



33122 Valle Road
 San Juan Capistrano, CA 92675 USA
 toll-free within U.S. 877.850.0805
 phone +1.949.369.8100
 fax +1.949.369.8105